



SECTORAL



FOOD

PRODUCT BROCHURE

THE INDISPENSABLE PART OF SYSTEM



IN FOOD INDUSTRIES
OUR PRODUCTS SUITABLE FOR USE

+ WHAT IS NSF?



NSF Certificate is a certification that shows that hygienic conditions are provided in food and fishery products and is valid almost all over the world. Established in 1944, NSF (National Foundation for Sanitation / Hygiene) operates on a global scale and its primary purpose is to protect public health. Products bearing the NSF certification mark meet all standard requirements, including product testing and regular inspections to verify that products continue to conform to the standard.

MULTIFUNCTIONAL CLEANING SPRAY H1/K1



Article Number: W170 126

It is the ideal cleaning for places to direct food supplies, with food. Very high effect in cleaning grease and oil, removes excessive cleaning and oil.



FOOD LUBRICATION SPRAY 400ml



Article Number: W160 105

Food lubrication spray is special lubrication. It has a light color and good adhesion. Used on most surfaces. It is resistant to water and oxide. and especially provides good protection against corrosion. It is used in the lubrication of various parts of meat, vegetable, fruit, fish machines in food and bottling machines, milk, soda, breweries. It is tasteless and odorless, does not harm human health. Do not over-lubricate when not needed. Approvals have been tested in Nordrhein Westfalen, Germany, if LMBG Food Lubricant Spray is used correctly.



MULTIFUNCTIONAL LUBRICATION SPRAY (H1)



Article Number: W150 221

Physiologically harmless synthetic oil with a multi-purpose additive blend for use in the foodstuffs industry. It has NSF H1 registration. It is effective against rust and corrosion. It has good lubricating properties. It infiltrates into dirt, oil and oil residues. It forms a thin adhesive protective film that protects even the smallest imperfections against moisture. It is resistant to water and humidity.



SILICONE GREASE H1 - 1 KG



Article Number: W150 210-1

It is NSF H1 fully synthetic silicone oil developed for food. It has high thermal temperature, has excellent performance against water and steam up to +140°C, has high viscosity base oils and has a very good structure. Ideal for plastic-plastic, metal-plastic, ceramic-plastic and ceramic-plastic packaging; Compatible with most plastics and elastomers, including PC and EPDM.



FOOD GREASE



Article Number: W150 204

Wide-ranging application is characterized by excellent water and walking resistance. It is combined with high oxidation resistance and high dripping. It has very good anti-corrosion properties. It is physiologically harmless, odorless and tasteless. It is non-toxic and does not pose a danger to human health. This oil is approved by the Chemical Control Center LMBG in Nordrhein Westfalen. It is resistant to 250°C heat at the lubrication points of high-temperature bearings.



HAND CLEANING CREAM 30 L

Article Number: W140 603-30

Hand cleaning cream removes the most stubborn dirt, oil, grease, tar, pitch, coal grinding dust and residues. It is an alkaline and solvent-free hand cleaner with dermatologically safe ingredients. The fine abrasives it contains provide deep pore cleaning and gentleness.



WINOL UNIVERSAL BIO REINIGER

Article Number: W170 120

It is used for cleaning machinery, floors, all kinds of surfaces, plastics and upholstery. It does not cause staining or matting after drying. It can be diluted 1/5 according to the condition of dirt and oil. It is biodegradable and non-flammable. It is used in all kinds of machine and floor cleaning. It can also be used with a pressure pump.



STAINLESS STEEL- MAINTENANCE SPRAY

Article Number: W150 152

It provides cleaning, care and protection on all stainless metal surfaces. Eliminates rust and water marks. It also provides protection against fingerprint formation. It is used for polishing and protecting all kinds of stainless surfaces. Cleaning of kitchen and sanitary places, hotel, airport, office, industry, etc. used in the fields.



INSULATING VARNISH SPRAY RED 400ml

Article Number: W150 148

The insulation varnish complies with the standards with its high insulation value (resistance of 6*1010 Ohm in accordance with DIN 53482). It is resistant to bad weather conditions and corrosion. It creates a water-resistant protection layer. It dries immediately and gives positive results, especially in areas where this type of use is difficult.



COOLING SPRAY 500ml

Article Number: W170 121

Thanks to its content, it instantly cools down to -65°C. It does not conduct electric current. It cools industrial and production machines quickly and for a long time. Coolant spray shrinks metals and chains and offers easy assembly.



ZINK SPRAY LIGHT

Article Number: W140 443

Fast drying structure against corrosion with excellent long lasting effect for metals, dry film more than 90% zinc and zinc compounds. Adheres to almost all metals. Suitable for coating and repairing zinc layers, interlayer conductive as spot welding, primary layer for drilling, cutting and welding points, installations exposed to moisture.



CHROME-GLOSS SPRAY 400ml

Article Number: W140 441

Shiny chrome effect aluminum coating, resistant to 800 °C heat. It provides very good protection against corrosion. It is used to protect the visuality of metals. It does not contain heavy metals. It passes electric current. Thanks to the coating it forms on the surface, there is no need for polishing.



STAINLESS STEEL REPAIR SPRAY 400ml

Article Number: W140 448

It is used for crack detection on welded metal surfaces. The welded surface is cleaned with (Reiniger-Green). Then it is applied to the surface (Red). It is cleaned again (Reiniger-Green) after about 5 minutes. Crack is detected by tightening last (White).



SEAL REMOVER SPRAY 400ml

Article Number: W170 100

Remove paint, adhesive, gasket, etc. It can be used as oil, resin, paste solvent while easily dissolving it. It especially removes gaskets from pumps etc. It dissolves old polishes from most surfaces. It is used on wood, metal, glass and ceramics.



PROTECTIVE WAX SPRAY 400ml

Article Number: W160 106

It prevents the formation of rust by protecting against corrosion in all metals, machinery and equipment. It creates a thin wax layer on the surface. Resistant to water and salt water vapor. Easy to use and remove.



PRO 1W40 SUPER GLUE

Article Number: W140 603-30

Suitable for plastic, rubber, steel metals, orings, etc. It sticks in 1-3 seconds. It has medium viscosity.



MDF INSTANT ADHESIVE 400ml

Article Number: W200 022

It is a two component fast curing aerosol type adhesive. It adheres harmoniously to many surfaces such as metal, wood, plastic. Cures fast. It provides a strong bonding. It is applied easily. It provides harmonious adhesion with all surfaces. (including rough surfaces)



AUTOMATIC SILICONE SEALANT GREY 200ml

Article Number: W200 505

It is an acetate-based elastic one-component liquid sealant. It creates a high and permanent elastic seal with its very good adhesion to the materials used. Gasketing is resistant to changing weather conditions, UV rays, hot water, oil and grease, etc. resistant to influences.



ADHESIVE IMPERMEABLE WHITE 300ml

Article Number: W160 261-B

Adhesive, impermeable, single component, is a strong adhesive and filling material based on polyurethane. It dries with the humidity of the air. Usage Areas: It is used without primer on materials such as glass porcelain, aluminum, steel, PVC, wood concrete. It is recommended to use sandpaper on auto body joints, caravan container joints, ship constructions, shiny surfaces.



STRONG RUST REMOVER

Article Number: 400 ML: W160 170 / 200 ML: W160 120

It is a mineral oil based rust remover with excellent friction properties, provides superior rust penetration and high rust solution. MoS₂ reduces friction very well due to solid lubricants. It does not contain resin, silicone and acid. Corrosion protection is good and long lasting.



INSULATING VARNISH SPRAY

Article Number: W150 149

The insulation varnish complies with the standards with its high insulation value (resistance of 6*10¹⁰ Ohm in accordance with DIN 53482). It is resistant to bad weather conditions and corrosion. It creates a water-resistant protection layer. It dries immediately and gives positive results, especially in areas where this type of use is difficult.



WW3000 LIQUID GREASE SPRAY 500ml

Article Number: W160 114

It is a lubricating product. It is resistant to high pressure. It is resistant to corrosion, water and 180°C temperature. Adhesion is much more. It does not flow or drip. It makes transparent and permanent lubrication.



V BELT SPRAY 400ml

Article Number: W150 157

Minimizes squeaking and slipping of the V-belt, keeping it flexible and extending their life. While protecting belts and pulleys against wear, it increases efficiency and pulling power and provides protection.



MOS2 DRY LUBRICATION SPRAY 400ml

Article Number: W160 109

It is used where grease lubrication is not possible. It reduces metal-to-metal friction. It prevents corrosion between dissimilar metals. It has very good thermal conductivity. It is resistant to high pressure.



CONTACT SPRAY (NON-OIL) 400ml

Article Number: W170 109

It is a versatile spray among mineral oil-based organic solvents. It is used for cleaning electronic cards and sockets. It prevents leakage electricity and power loss. Contacts, fuses, wiring, etc. It removes oxidation and sulfide layers.



2W43 THREADLOCKER MEDIUM 50 ML

Article Number: 20303

WINKEL PRO 2W43 is a medium strength part product developed for fixing and all kinds of connection connection. Proposition about the product metal and preparation against air-less heating cures. It reacts faster on iron.



PRO 2W701 THREADLOCKER HIGH 250

Article Number: W20307

WINKEL PRO 2W701 is an oil-resistant and high-strength adhesive product developed for fixing and sealing metal screws. When the product is applied between metal connections and in the absence of air, it cures by reacting. It has a temperature resistance up to 180 ° C. It ensures that the stud bolts are fixed without dismantling the roller bearings. It is especially ideal for screw connections that are subjected to heavy loads. It can also be used on slightly soiled surfaces.



6W20 RETAINING HIGH TEMPERATURE 250 ML

Article Number: W20601

WINKEL PRO 6W20 is a hot oil resistant and high-strength clumper developed especially for passive surfaces. When the product is applied between metal connections and in the absence of air, it cures by reacting. It works well on cylindrical parts to be assembled and on slightly dirty surfaces.



6W48 RETAINING HIGH TEMP&CHEMICALS 50 ML

Article Number: 20609

WINKEL PRO 6W48 is a high-strength clumper that makes it possible to fix cylindrical joints without particularly cleaning. The product cures when applied between metal connections and reacts in an airless environment. It has temperature resistance up to 180°C.



2W22 THREADLOCKER LOW STRENGTH 50 ML

Article Number: W20300

WINKEL PRO 2W22 is a low-strength, removable, anaerobic adhesive developed for fixing and sealing all kinds of bolt connections. When the product is applied between metal connections and in the absence of air, it cures by reacting. Drying speed in active metals, stainless, chrome, etc. It is faster than passive metals. It has high resistance to vibration, oil and temperature up to 180 ° C. When necessary, it can be easily removed with standard hand tools.



5W77 THREADSEALANT PTFE MEDIUM

Article Number: W20403

WINKEL PRO 5W77 is a medium strength gear sealant developed for parallel and bevel gears and their combinations. The product cures when applied between metal gears and reacts in an airless environment. It has temperature resistance up to +180°C. Unlike conventional materials such as linen, PTFE, it provides reliable sealing.



6W41 RETAINING MEDIUM 50 ML

Article Number: W20606

WINKEL PRO 6W41 is a medium strength conventional clamp developed especially for cylindrical joints. When the product is applied between metal connections and in the absence of air, it cures by reacting. It is widely used for fixing bearings, bushing bearings and rotating parts to gear wheels that need to be disassembled and installed frequently.

